

PRODOTTO

WALL BOX 1 SOCKET TYPE 2 22kW TA+RFID+LC

205.W35-D0



FEATURES

- Charge in mode 3 with pwm circuit pilot
- Identification of connected cord-set size
- Protection against direct contact Safety Child Shutters
- Current consumption metering
- Identification of authorized user
- Managing of latching system
- Charge managing in case of power outage
- Working in mode stand-alone free or personal
- Predisposition for serial communication


EQUIPMENT

- 1 terminal strip 5x10mm²
- 1 current transformer
- 1 modular contactor 4P 40A 24Vdc
- 1 DC Leakage detector
- 1 fuse holder 1P+N gG 4A
- 1 power supply 24Vdc 36W
- 1 control card
- 1 lcd display 2x20 rows backlight
- 1 reader RFID 13,56MHz
- 1 RBG led stripes
- 1 stop charge push-button (mode free)
- 1 backup battery

EXCLUDED

- 1 circuit breaker 3P+N C40 30mA ist. A

SIZE



TECHNICAL SPECIFICATIONS

PROTECTION DEGREE IP	IP54
WORKING FREQUENCY	50/60Hz
MOUNTING VERSION	SURFACE MOUNTING
MATERIAL	ENGINEERING PLASTIC
SYNTHETICAL DESCRIPTION	WALL BOX 1 SOCKET TYPE 2
GLOW WIRE	GW 650°C
PROTECTION DEGREE IK	IK08
RATED VOLTAGE	400V
POLES	3P+N+E
RATED CURRENT	32A
EV STANDARD	Type 2 3P+N+E 32A 400V~ 22kW
WORKING TEMPERATURE	-30°C/+50°C
COLOUR	ANTHRACITE

COMMERCIAL SERIES

BE-W Series

DIMENSIONS

235x370x115mm
